

A single (associated) waypoint example by GraphHopper Locus gpx 1.1 out.
Black = Actual V3.30.0 Red = NEW !

gpx:

```
<wpt lat="51.053843" lon="3.999352">
<ele>6.16</ele>
<time>2018-03-16T11:09:23.741Z</time>
<name>rechts</name>            (local language)
<cmt>Gratiebossen</cmt>      (rteStreet) (local language)
<desc>Onverhard</desc>      [EN] Unpaved = optional ! (local language)
<sym>right</sym>            (English !)
<extensions>                (At gpx1.0 out = removed!)
<locus:rteDistance>371.73187</locus:rteDistance>
<locus:rteTime>111</locus:rteTime>
<locus:rteSpeed>3.3489358</locus:rteSpeed>
<locus:rteStreet>Gratiebossen</locus:rteStreet>
<locus:rtePointAction>right</locus:rtePointAction>
</extensions>
</wpt>
```

tcx:

```
<CoursePoint>
<Name>Right</Name> => <Name>Rechts</Name>            (local language)
<Time>2018-03-16T11:09:23Z</Time>
<Position>
<LatitudeDegrees>51.053843</LatitudeDegrees>
<LongitudeDegrees>3.999352</LongitudeDegrees>
</Position>
<AltitudeMeters>6.16</AltitudeMeters>
<PointType>Right</PointType>                        (English !)
<Notes>rechts</Notes> => <Notes>Gratiebossen</Notes> (rteStreet) (local language)
</CoursePoint>
```